

BPS CONCRETE COATING
BPS CEMENT FLOOR COATING



"LOOK INTO IT"

slip-top cans - all sizes
 easy to open - self-sealing
 clean-convenient-no waste


BEST PAINT SOLD

For Mailing
 Attach
 Postage Stamp
 Here

BPS Concrete Coating



CREAM WHITE




LIGHT CANARY



IVORY



COLONIAL YELLOW




WARM DRAB




DARK OLIVE



LIGHT GRAY



OLIVE GRAY



FRENCH GRAY



GRAY STONE



LIGHT OLIVE



RICH RED

Cream White, shown on this card, should not be confused with our **Regular White**, carried in stock in addition to the twelve shades shown on the card.

BPS Concrete Coating

For Use Upon All Concrete Surfaces,
Interior or Exterior

PRODUCES a uniform, flat, durable finish, which successfully prevents disintegration and checking. Shuts out all moisture and is unaffected by the natural alkali in the cement or concrete.

It dries very hard, combining with and becoming a part of the concrete. Prevents the surface from disintegrating and also prevents moisture and discoloration.

Also for brick and other surfaces where a flat finish is desired.

Covering Capacity - Concrete or Brick Surfaces - one coat - About 150 to 200 square feet to the gallon. Close-grained surfaces, such as adamant, plaster, etc. - one coat - 200 to 300 square feet to the gallon.

DIRECTIONS FOR USE

BPS Concrete Coating

Stir thoroly until of even consistency. See that the surface is thoroly cleaned of all loose material. For **priming coat**, reduce with half gallon of pure raw linseed oil to the gallon of paint. **Second coat**, apply BPS Concrete Coating as it comes in the package. Sufficient time should be allowed for the surface to dry out thoroly before applying any paint.

For Cement Floors, use BPS Cement Floor Coating.


BPS Cement Floor Coating

For Interior Cement and Wood Floors


Dries over night with a rich, durable gloss




LIGHT LEAD




SLATE



DUST



RED



GREEN




FAWN




LIGHT YELLOW



YELLOW



LIGHT BROWN



MAROON

BPS Cement Floor Coating

For

Interior Cement and Wood Floors

PREVENTS and stops disintegration and "powdering off" of the cement.

Does away with the poisonous alkali dust continually arising from these surfaces. It thoroly impregnates the surface, so that it prevents absorption of grease, oil and moisture, and produces a tile-like finish which can be washed or scrubbed and kept as clean as the most expensive tile floor.

Dries hard over night with a tough, elastic, durable gloss surface.

Covering Capacity - One Coat, about 600 square feet to the gallon. **Two Coats**, about 325 square feet to the gallon.

DIRECTIONS FOR USE

BPS Cement Floor Coating

Stir BPS Cement Floor Coating thoroly before using and pour it back and forth from can to can.

See that the floor is free from grease, dry and clean. For the first and second coats, add one part of pure turpentine to three parts of paint. Apply third coat as it comes in the can.

Spread the paint out thin and evenly over the entire surface and allow it to become perfectly hard between coats. Leave the windows and doors open, as free circulation of air is absolutely necessary to insure the proper drying of the paint.

Made in The United States



TRADE MARK REGISTERED

**CONCRETE
COATING
AND
CEMENT FLOOR
COATING**

MANUFACTURED BY

The Patterson-Sargent Co.

Cleveland Chicago New York Kansas City
St. Paul Detroit Long Island City Boston
Sioux City Fort Worth Jacksonville

Made in The United States



Digitized by ASSOCIATION FOR PRESERVATION TECHNOLOGY, www.apti.org for the
BUILDING TECHNOLOGY HERITAGE LIBRARY
<https://archive.org/details/buildingtechnologyheritagelibrary>

From the collection of

Tulane University: Southeastern Architectural Archive <http://seaa.tulane.edu>

The P
Cleveland
St. Paul
Sioux C

TE
NG
LOOR
NG
BY
gent Co.
k Kansas City
d City Boston
Jacksonville